

DEVELOPMENT AND CHARACTERIZATION OF EXTERIOR RADIATA-PINE CLADDING FOR MORE SUSTAINABLE AND ENERGY EFFICIENT FAÇADES IN THE BASQUE COUNTRY

Ph.D. THESIS

presented to obtain the degree of
Doctor Philosophy in Industrial Engineering

Belinda Pelaz Sánchez



DIRECTORS

Dr. Jesús Cuadrado Rojo
Dr. Jesús M^a Blanco Ilzarbe

April 2017, Bilbao

Mechanical Engineering Department



Universidad del País Vasco
Euskal Herriko Unibertsitatea



Ingeniaritza Goi Eskola Teknikoa
Escuela Técnica Superior de Ingeniería
Bilbao

*Development and
characterization of exterior
Radiata-pine cladding for more
sustainable and energy efficient
façades in the Basque Country*

Doctoral Thesis

March 2017

Author: Belinda Pelaz Sánchez

Directors: Jesús Cuadrado Rojo y
Jesús M^a Blanco Ilzarbe

eman ta zabal zazu



Universidad
del País Vasco

Euskal Herriko
Unibertsitatea



Ingeniaritza Goi Eskola Teknikoa
Escuela Técnica Superior de Ingeniería
Bilbao

Acknowledgements

I would like to express the deepest appreciation to my thesis directors, Jesús and Jesús M^a, for their help and availability, and to the Department of Mechanical Engineering, School of Engineering, UPV/EHU for their confidence.

I gratefully acknowledge the funding provided by the Basque Regional Government through IT781-13, UPV/EHU under program UFI 11/29, and ITeCons (Institute for Research and Technological Development in Construction, Energy, Environment and Sustainability), University of Coimbra (UC).

In addition, I also thank for the grant received from the Department of Economy and Competitiveness of the Basque Regional Government (EJ-GV) to the project: “*Fomento uso madera pino radiata en fachadas edificios*”, and the Erasmus+ Doctorate grant (UPV/EHU).

Above all, I would like to thank my husband for his personal support and patience. My parents, brother and sister have given me their unequivocal support throughout, as always, for which my mere expression of thanks likewise does not suffice. To friends and others who in one way or another shared their morally support, thank you.

Contents

0	Introduction	21
0.1	Aims	23
1	State of Art	27
1.1	Evolution of façades.....	28
1.1.1	Façade materials.....	34
1.1.2	Design requirements.....	44
1.1.3	Use requirements	46
1.2	Thermal resistance in façades.....	47
1.2.1	Thermal behaviour of wooden façades	49
1.2.2	Thermal properties of Radiata-pine.....	50
1.3	Wood natural durability.....	52
1.3.1	Wood protection.....	53
1.4	Sustainable construction.....	55
1.4.1	Characteristics of the environment	59
2	Methodology.....	67
2.1	Test box procedure	69
2.1.1	Equipment.....	75
2.1.2	Obtaining the thermal conductivity.....	77
3	Thermal characterization of Radiata-pine.....	83

3.1	Introduction to heat transfer.....	85
3.2	Radiata-pine conductivity.....	88
3.2.1	Thermal characterization of Radiata-pine by conduction	90
3.2.2	Thermal characterization of Radiata-pine by convection: Test box	93
3.3	Specific heat	113
3.4	Water vapour diffusion.....	116
3.5	Conclusions.....	121
4	Energy simulation	127
4.1	Energy Simulation with THERM v.7.3	128
4.1.1	Exterior cladding simulation.....	129
4.1.2	Clearances in tongue-and-groove wooden boards	136
4.2	Hygrothermal simulation with WUFI Pro v.5.3.....	145
4.2.1	Radiata-pine simulation.....	147
4.2.2	Wooden façade hygrothermal behaviour	149
4.3	Computational fluid dynamics with Design Builder.....	153
4.4	Conclusions.....	156
5	Durability.....	161
5.1	Test preparation	163
5.2	Registration of climate data	166
5.3	Weathering analysis	174
5.3.1	Emissivity.....	186
5.4	Thermal conductivity.....	188
5.5	Conclusions.....	190
6	Sustainability.....	193
6.1	Assessment model for environmentally friendly cladding	194
6.1.1	Analytical Framework.....	194
6.1.2	Evaluation methodology	195
6.1.3	Development of the tree.....	197
6.1.4	Value functions.....	198
6.1.5	Weighting factors	199

6.1.6	Definition of criteria and indicators.....	202
6.1.7	Evaluation of alternatives through the environmental sustainability index (ESI-CW) 212	
6.2	Case study and sensitivity analysis	213
6.3	Conclusions	217
7	Wooden façades catalogue	221
7.1	Analysis of facades.....	222
7.1.1	Comparison of façades	248
7.2	Conclusions	249
8	Conclusions	253
8.1	Suggestions of future research	259
	References	263

Tables

Table 1.1. Façade requirements.....	45
Table 1.2. Advantages and drawbacks of wooden façade	47
Table 1.3. Wood thermal properties, ISO UNE-EN 10456 standard	50
Table 1.4. Wood thermal conductivity according to CTE norm	51
Table 1.5. Terminology applied to sustainable buildings.....	58
Table 1.6. Climate data from Bilbao.....	60
Table 2.1. Interior and exterior superficial thermal resistance (R_{si} , R_{se}) [$(m^2 \cdot ^\circ C)/W$]	74
Table 2.2. Technical specifications of test equipment	76
Table 3.1. Class of use to wooden elements.....	89
Table 3.2. Protection requirements and penetration class (CP)	90
Table 3.3. Technical Specifications of λ -Meter EP-500 equipment.....	91
Table 3.4. Conductivity results by UNE-EN 12664	92
Table 3.5. Thermal conductivity of each sample, gradient 10 and 15°C (λ_{10} , λ_{15}).....	93
Table 3.6. Technical specifications of Testo 875-1i infrared camera	99
Table 3.7. Natural wood data of temperatures and conductivity.....	104
Table 3.8. Chemical treated wood data of temperatures and conductivity	105
Table 3.9. Heat-treated wood data of temperatures and conductivity.....	106

Table 3.10. Technical specifications of Testo 435-1	109
Table 3.11. Transmittance obtained by TESTO equipment	110
Table 3.12. Transmittance obtained by test box procedure	111
Table 3.13. Estimation of humidity content for each sample.....	112
Table 3.14. Technical specifications of NETZSCH DSC 200 F3 Maia.....	114
Table 3.15. Specific heat of Radiata pine.....	114
Table 3.16. Thermal mass (mt) and inertia (I) of each sample	115
Table 3.17. Permeability properties of Sample 1, natural Radiata-pine.....	119
Table 3.18. Permeability properties of Sample 2, chemical treated Radiata-pine	119
Table 3.19. Permeability properties of Sample 3, heat-treated Radiata-pine.....	119
Table 3.20. Conductivity and diffusion factor results	120
Table 4.1. Tongue-and-groove wooden boards, design D1	131
Table 4.2. Tongue-and-groove wooden boards, design D2	131
Table 4.3. Tongue-and-groove wooden boards, design D3	132
Table 4.4. Tongue-and-groove wooden boards, design D4	132
Table 4.5. Tongue-and-groove wooden boards, design D5.....	133
Table 4.6. Thermal resistance resulted by each solution, D1, D2, D3, D4 and D5.....	134
Table 4.7. Area and perimeter exposed to exterior for D1, D2, D3, D4 and D5	134
Table 4.8. Energy simulation results for each case.....	141
Table 4.9. Simulation results for Radiata-pine cladding	142
Table 4.10. Thermographic camera specifications	144
Table 4.11. Emissivity estimation of the wooden boards.....	144
Table 4.12. Definition of sample 1, 2 and 3 properties	147
Table 4.13. Sample 1, 2 and 3 conductivity depending on test.....	148
Table 4.14. Transmittance (U) and superficial resistance (Rs) values obtained by Test Box	148
Table 4.15. Transient transmittance results by WUFI Pro (U_T).....	149
Table 4.16. Transmittance in case 1 (U1), 2 (U2) and 3 (U3)	151

Table 4.17. Design Builder results for sample S1, to 28°C Test.....	154
Table 4.18. Design Builder results and lost in relation with box thermal resistance	154
Table 5.1. Climate data from 23/12/2014 to 23/03/2015	169
Table 5.2. Climate data from 23/03/2015 to 23/06/2015	169
Table 5.3. Climate data from 23/06/2015 to 23/09/2015	170
Table 5.4. Climate data from 23/09/2015 to 23/12/2015	171
Table 5.5. Climate data from 23/12/2015 to 23/03/2016	171
Table 5.6. Climate data from 23/03/2016 to 23/06/2016	172
Table 5.7. Climate data from 23/06/2016 to 23/09/2016	173
Table 5.8. Climate data from 23/09/2016 to 23/12/2016	173
Table 5.9. Visual assessment of the samples ageing, from January to March, 2015	176
Table 5.10. Visual assessment of the samples ageing, from April to June, 2015	177
Table 5.11. Visual assessment of the samples ageing, from July to September, 2015	178
Table 5.12. Visual assessment of the samples ageing, from October to December, 2015	179
Table 5.13. Visual assessment of the samples ageing, from January to March, 2016	180
Table 5.14. Visual assessment of the samples ageing, from April to June, 2016	181
Table 5.15. Visual assessment of the samples ageing, from July to September, 2016	182
Table 5.16. Visual assessment of the samples ageing, from October to December, 2016	183
Table 5.17. Reference temperature (T_0), material temperature (T) and emissivity (ϵ) of P1, P2 and P3	187
Table 5.18. Emissivity variation in sample 1, 2 and 3 before and after ageing	188
Table 5.19. Thermal conductivity variation between original (λ) and elder samples (λ')	189
Table 6.1. Scoring of the “Product Characterization” indicator	203
Table 6.2. Scoring of the “Manufacturing and assembly” indicator	206
Table 6.3. Score of “Optimization of resources” indicator	208
Table 6.4. Scoring of “Impact Control” indicator	209
Table 6.5. Scoring of “Waste Management” indicator	211

Table 6.6. Practical valuation, Case 1	214
Table 6.7. Practical valuation, Case 2	215
Table 6.8. Practical valuation, Case 3	216

Figures

Figure 1.1. Different facade models.....	32
Figure 1.2. Santa Maria del Fiore © E. Buchot.....	35
Figure 1.3. House Ratschow in Rostock © Bernd H. Schuldes	37
Figure 1.4. Frank Lloyd Wright designer ©2014 Ennis House Foundation	39
Figure 1.5. Red House, Ross-shire @Brennan & Wilson Architects	43
Figure 1.6. Aspects of sustainable construction	56
Figure 1.7. Olgyay bioclimatic chart applied to Bilbao, from January (J) to December (D) ..	61
Figure 1.8. Givoni bioclimatic chart applied to Bilbao, from January (J) to December (D) ...	63
Figure 2.1. Graphical abstract of the research.....	68
Figure 2.2. Test box photographs	70
Figure 2.3. Heat loss percentages	73
Figure 2.4. Superficial thermal resistance from the exterior side.....	74
Figure 2.5. Heat transfer through a plane sample	77
Figure 3.1. Combinations of heat transfer in a plane.....	86
Figure 3.2. Heat transfer through a ventilated façade.....	86
Figure 3.3. CTE climate zones in Spain	87

Figure 3.4. λ -Meter EP-500, thermal conductivity measure equipment 91

Figure 3.5. Velocity and temperature profile for the natural convection flux on a hot vertical slab with T_s temperature inside a fluid with T_∞ temperature 95

Figure 3.6. Natural convection: Isotherms on a hot plate 96

Figure 3.7. Infrared Camera with Super Resolution ©TESTO 875-1i 99

Figure 3.8. Natural (1), chemical treated (2) and heat-treated (3) Radiata-pine thermography 99

Figure 3.9. Multifunctional transmittance detector © TESTO 435-1 with thermocouples and a wireless temperature probe 109

Figure 3.10. NETZSCH DSC 200 F3 Maia equipment 113

Figure 3.11. Chemical treated Radiata-pine samples 114

Figure 3.12. Preparation of the permeability test step by step 118

Figure 3.13. Relative humidity measures for natural (a) and heat-treated wood (b) 120

Figure 4.1. CLT (left) and timber framed (right) façades 130

Figure 4.2. Common tongue-and-groove wooden boards 136

Figure 4.3. Tongue-and-groove boards: Clearances and movements 137

Figure 4.4. Analysis of different distribution of clearances 138

Figure 4.5. Distribution of temperature 139

Figure 4.6. Distribution of heat flux 140

Figure 4.7. Distribution of heat flux across Radiata-pine cladding 142

Figure 4.8. Wood wall test with a heat chamber 143

Figure 4.9. Thermography 144

Figure 4.10. Corporative logotype 145

Figure 4.11. Hygrothermal behaviour of case 1 during a year 152

Figure 4.12. CFD simulation of the test box 155

Figure 5.1. Natural wood (1), chemical treated (2) and heat-treated (3) Radiata-pine 162

Figure 5.2. Cylindrical solar chart, from June to December 164

Figure 5.3. Cylindrical solar chart, from December to June 164

Figure 5.4. Shading simulation of the test in January	165
Figure 5.5. The samples placement	166
Figure 5.6. Sample 1, before (a), after a year (b), after two years (c).....	184
Figure 5.7. Sample 2, before (a), after a year (b), after two years (c).....	184
Figure 5.8. Sample 3, before (a), after a year (b), after two years (c).....	185
Figure 5.9. Samples after rainy days, 04/09/2015	185
Figure 5.10. Reference termography ($\epsilon = 1$)	186
Figure 6.1. General Hierarchy Diagram of the Evaluation.....	197
Figure 6.2. Evaluation tree of the environmental sustainability index	200
Figure 6.3. Value function associated with the “Product Characterization” indicator	204
Figure 6.4. Value function of “Manufacture and Assembly” indicator	207
Figure 6.5. Value function of “Optimization of resources” indicator.....	208
Figure 6.6. Value function of “Impact Control” indicator	210
Figure 6.7. Value function of “Waste Management” indicator	212
Figure 6.8. Case study © A. Buruaga.....	213

Graphics

Graphic 3.1. Registration of temperatures during a test	101
Graphic 3.2. Three cycles interval of temperatures in each test (a, b, c and d).....	102
Graphic 3.3. Three cycles interval of temperatures in each test (a, b, c and d) for natural wood (right) and heat-treated wood (left)	103
Graphic 3.4. Thermal conductivity of Radiata-pine	107
Graphic 3.5. Thermal conductivity of Radiata-pine treated with chemicals.....	107
Graphic 3.6. Thermal conductivity of Radiata-pine heat-treated	107
Graphic 3.7. Thermal transmittance of sample 1, 2 and 3.....	108
Graphic 4.1. Transmittance in case 1 (U1), 2 (U2) and 3 (U3).....	151
Graphic 5.1. Climate data during 2015 in Bilbao	167
Graphic 5.2. Climate data during 2016 in Bilbao	168
Graphic 6.1. Results of Case 1	214
Graphic 6.2. Results of Case 2	215
Graphic 6.3. Results of Case 3	216

*"We may use wood with intelligence
only if we understood wood"*

Frank Lloyd Wright

1867-1959

CHAPTER **0**
Introduction
